

TECHNICAL SPECIFICATIONS – CAMRY-2012

SPECIFICATIONS	24V 3.5-litre (2GR-FE)	16V 2.5-litre (2AR-FE)
	G grade	N grade
TRANSMISSION	6-speed automatic	6-speed automatic
DIMENSIONS & WEIGHT		
Overall length (mm)	4825	
Overall width (mm)	1825	
Overall height (mm)	1480	
Wheelbase (mm)	2775	
Tread Front/Rear (mm)	1575/1565	
Ground Clearance (mm)	160	
Curb Weight (kg)	1525-1540	1435-1460
Gross Vehicle Weight (kg)	2100	
CHASSIS		
Suspension Front	MacPherson struts (L-shaped lower arms, gas-filled shock absorbers with a stabiliser bar)	
Rear	Dual link struts (Lower arms, gas-filled shock absorbers with a stabiliser bar)	
Brakes Front/Rear	Ventilated discs / Discs	
Min. Turning radius (Tyres) m	5.5	
Fuel Tank Capacity litres	70	
Tyres	215 / 55R17	215/60R16
ENGINES		
24V 3.5-litre (2GR-FE) 16V 2.5-litre (2AR-FE)		
Type	V6 Four Cam 24-Valve with Dual VVT-i	4 cyl. in-line Twin Cam 16-Valve with Dual VVT-i
Piston displacement cc	3456	2494
Max. Output (EEC) kW / rpm	204 / 6200	133 / 6000
Max. Torque (EEC) Nm / rpm	346/4700	231/4100
Fuel Sytem	Electronic Fuel Injection	Electronic Fuel Injection
A : Automatic transmission M :Manual transmission		